PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: (11) International Publication Number: WO 95/10571 C09D 11/18, C08L 91/02, B43K 7/01 (43) International Publication Date: 20 April 1995 (20.04.95) PCT/US94/11710 (81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, (21) International Application Number: CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NIL, PT, SE), OAPI (22) International Filing Date: 13 October 1994 (13.10.94) (30) Priority Data: 137,841 15 October 1993 (15.10.93) patent (BF, BJ, CF, CG, CL, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW, SD, SZ). (60) Parent Application or Grant Published (63) Related by Continuation 137,841 (CON) 15 October 1993 (15.10.93) With international search report. US Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of Filed on amendments. (71) Applicant (for all designated States except US): THE GILLETTE COMPANY [US/US]; Prudential Tower Building, Boston, MA 02199-4099 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): LOFIIN, Rachel, M. [US/US]; 9 Doris Road, Halifax, MA 02338-1149 (US). (74) Agents: HANDELMAN, Joseph, H. et al.; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US).

(54) Title: AQUEOUS INKS

(57) Abstract

A method of making an emulsion ink is provided. The method includes mixing an ink precursor and processing the ink precursor in a homogenizer to form an emulsion ink. The ink precursor includes a pigment, water, a film forming polymer, an oil and, preferably, a pH dependent thickener and a base.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MIR	Mauritania
ΑÜ	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Paso	HU	Hungary	NO	Norway
BG	Bulgaria	IB	Ireland	NZ	New Zealand
BJ	Benin	П	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KR	Kenya	RO	Romania
CA	Canada	KG	Kyrgystan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
CG	Congo		of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SI	Slovenia
CI	Côte d'Ivoire	KZ	Kazakhstan	SK	Slovakia
CM	Cameroon	LI	Liechtenstein	SN	Senegai
CN	China	LK ·	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
CZ	Czech Republic	LV	Latvia	TJ	Tajikistan
DE	Germany	MC	Monaco	TT	Trinidad and Tobago
DK	Demnark	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	US	United States of America
F	Finland	ML	Mali	UZ	Uzbekistan `
FR	France	MN	Mongolia	VN	Vict Nam
GA	Gabon	_	-		

- 1 -

AQUEOUS INKS

The present invention relates to ink compositions for use in pens, particularly ball-point pen inks.

5

10

15

20

25

While there are long-recognized advantages to using aqueous inks in ball point pens, the viscosity of these inks must be carefully adjusted in order to avoid flow problems, such as leakage around the ball. To adjust the viscosity, these inks have been thickened with natural gums, e.g., xanthan gum. Inks containing gums, however, often exhibit undesirable performance characteristics, such as blobbing and inadequate ink flow as the ink supply in the pen is depleted. Attempts have been made to overcome blobbing by using a very small ball, but pens having a small ball size tend to have a "scratchy feel" during use.

Aqueous inks also tend to lack smoothness, good writing consistency, and are prone to drying out at the ball tip when the pen is left uncapped.

The present invention features an aqueous ink which provides good permanency, long cap-off times, high writing intensity, smooth writing characteristics, consistent ink flow and long shelf life.

5

10

15

20

25

30

35

- 2 -

In one aspect, the invention features a method of making an ink having the aforementioned advantageous properties.

In one aspect, the method includes mixing an ink precursor and processing the ink precursor in a homogenizer, to form an emulsion ink. The ink precursor includes a film forming polymer, a pigment, water, and an oil.

Preferred precursors further include a pH dependent this tener, a base and an emulsifier. Advantageously, only low levels of emulsifier are typically necessar, due to the efficacy of the homogenizer in forming a stable microemulsion. In embodiments which include a pH dependent thickener and a base, the film forming polymer may be omitted, although this is not generally preferred, as it tends to reduce the permanency of markings made with the ink.

The homogenizer preferably includes a liquid jet interaction chamber in which the leading edges of a plurality of sheets of a liquid mixture are forced under pressure to impinge in a low-pressure turbulent zone of the liquid. Preferred devices include a plurality of nozzles having elongated orifices to eject under pressure sheets of the liquid, the nozzles being arranged to effect impingement of the sheets along a common liquid jet interaction front. Suitable homogenizers of this type are described in U.S. Patents 4,908,154 and 4,533,254, the disclosures of which are incorporated herein by reference.

In another aspect, the method includes mixing an oil and water, processing the mixture in a homogenizer to form an oil-in-water microemulsion, and adding the oil-in-water microemulsion to an ink comprising a film

5

10

15

20

25

30

35

- 3 -

forming polymer, a pigment and water. In more preferred embodiments, the ink further includes a pH dependent thickener and a base, and an emulsifier is added to the oil and water mixture prior to forming the microemulsion.

In another aspect, the invention features an ink composition including a pigment, water, an pH dependent thickener and a base. Preferably, the composition further includes a film forming polymer. Preferred compositions provide good ink flow control, permanence and water resistance.

In a further aspect, the invention features an ink composition including a film forming polymer, a pigment, water, and an oil. This composition provides particularly good writing smoothness, long cap off times, permanence and water resistance.

In preferred embodiments, the ink composition, in addition to a film forming polymer, water, and pigment, includes both an oil and the combination of pH dependent thickener and base. In preferred compositions, the oil is selected from drying and semi-drying oils, and the polymer is an acrylic polymer. These compositions provide a good balance of properties.

The term "pH dependent thickener", as used herein, refers to a material which, when added to a composition, thickens the composition only if the composition has a pH of greater than about 7, preferably between about 8 and 10. These thickeners are also referred to in the art as "associative thickeners". While not being bound by any theory, it is believed that these thickeners cause the viscosity of the ink to increase because the thickener itself swells

- 4 -

when contacted by a base.

5

10

15

20

25

30

The term "emulsifier", as used herein, refers to an additive which enhances the ability of a composition to form an emulsion. The term is intended to include surfactants and other conventional types of emulsifiers.

The term "microemulsion", as used herein, refers to an emulsion, i.e., a microscopically heterogeneous mixture comprising minute droplets of a first liquid suspended in a second liquid, in which the suspended droplets have a very small, uniform particle size, typically less than about one micron. The verb "microemulsify", as used herein, refers to processing a solution to form a microemulsion, and "homogenizer" refers to any device capable of forming a microemulsion.

The term "drying oil", as used herein, refers to an oil which crosslinks and forms a dry film by oxidation. The term "semi-drying oil" refers to an oil which slowly thickens as a result of oxidation.

Other features and advantages of the invention will be apparent from the Description of the Preferred Embodiments thereof, and from the claims.

A preferred ink includes a film-forming acrylic polymer, a lubricating oil, more preferably a drying or semi-drying oil, a pH dependent thickener, a base, a pigment, an emulsifier, and water. An emulsion ink is formed by premixing these ingredients and processing them through a homogenizer to form a microemulsion.

The acrylic polymer is preferably provided in the form of an emulsion. However, if desired, a water soluble acrylic may be used.

5

10

15

20

25

30

35

- 5 -

A portion of the acrylic polymer may be included with the pigment in a pigment dispersion which contains an acrylic polymer as the medium in which the pigment is dispersed. Preferred acrylic polymers include thermoplastic acrylics, e.g., polymethacrylates, such as polymethyl methacrylate and other methyl acrylates. A preferred acrylic emulsion is RHOPLEX® AC-261 emulsion, available from Rohm and Haas Co., Philadelphia, PA. RHOPLEX AC 261 is an all-acrylic co-polymer combination, a butyl acrylate/methyl methacrylate blend having a low acid content, a molecular weight of around 1,000,000 and a glass transition temperature of between 15 and 20. Preferred compositions contain from about 5 to 30 weight percent of the acrylic polymer, more preferably from 10 to 20 weight percent. Too much of the acrylic may result in undesirably high viscosity at an effective level of pigment, while too little may result in an ink having poor water resistance when dry.

Suitable drying and semi-drying oils include vegetable oils, e.g., linseed (drying), safflower (drying), cottonseed (semi-drying), and corn (semi-drying), with linseed being preferred. Instead of drying or semi-drying oils, other lubricating oils, e.g., silicones, may be used. These other oils, however, may tend to increase the drying time of the ink. Preferably, the composition contains from about 10 to 25 weight percent of the oil, more preferably about 15 weight percent. The oil imparts both lubricity and good cap-off properties to the ink. Too much oil may cause the ink to dry too slowly, while too little oil may not impart the desired lubricity and cap-off

The oil may be added to the ink properties. composition prior to microemulsifying the composition, or the oil and a portion of the water can be separately microemulsified prior to addition to the composition, either in addition to or instead of microemulsifying the entire composition. If the oil and water are separately microemulsified, it is generally preferred that the ratio of oil to water in the

10 microemulsion be from about 1:5 to 2:5.

5

15

20

25

30

35

The pH dependent thickener is preferably an acid stabilized acrylic resin. Suitable of dependent thickeners are commercially available from Union Carbide under the tradename POLYPHOBE, and ALCO gum thickeners, available from Alco Company. POLYPHOBE 9823 acrylic latex thickener is preferred. Preferably, the composition contains from about 1 to 5 weight percent of the thickener, more preferably about 2 weight percent. Higher levels of thickener may result in undesirably high viscosity, while lower levels may not provide adequate flow control. In embodiments in which the ink composition does not include a film forming polymer, it is typically preferred to use levels of thickener at the high end of the preferred range, to provide adequate viscosity.

In order for the pH dependent thickener to effectively thicken the composition, it is necessary for the composition to have a relatively high pH, e.g., at least 7 and preferably 8 to 10. The pH of the composition may be raised by adding a base, e.g., ammonia or 2-amino-2-methyl-1-propanol (AMP), to the composition as a separate ingredient. Alternatively, the pigment may be

5

10

15

20

25 ·

30

35

- 7 .

provided in the form of a pigment dispersion containing a base, and/or the polymer in the form of a polymer emulsion containing a base, as do the preferred pigment dispersions and polymer emulsions described herein. Preferably, the composition contains a sufficient amount of base, whether provided as a separate ingredient or included in the other components, to raise the pH of the composition to the preferred level.

Enough pigment should be included in the ink to provide an adequate color intensity, but not so much that viscosity becomes excessively high. The preferred inks include between approximately 2% and 10% pigment by weight, more preferably between approximately 4% and 8%. Pigments that may be used in the invention include water dispersible pigments, and preferably the pigment is provided in the form of an aqueous dispersion, for accurate measurement and uniform mixing. Suitable dispersions include those available from Hoechst Celanese under the tradename FLEXONYL or HOSTAFINE, those available from KVK U.S.A. Inc. under the tradename PREDISOL, those available from Heucotech Ltd. under the tradename HEUCOSPERSE, those available from Nippon Keiko Kagaku, Ltd. under the tradename LUMIKOL, and those available from Mikuni Color Works, Inc. under the tradename TITICACA. A preferred pigment dispersion is HEUCOSPERSE III dispersion. The total amount of the pigment dispersion to be added will depend upon the solids level of the dispersion, and will be selected to give an effective amount of the pigment, as described above. It is preferred that the pigment have a relatively small

5

10

15

20

25

30

35

- 8 -

particle size, preferably less than 0.5 micron, to prevent settling. The small particle size also prevents clogging of the pen point.

The emulsifier serves to stabilize the oil-in-water microemulsion. Suitable emulsifiers include most conventional emulsifiers in particular those suitable for emulsifying vegetable oils. Preferably, the emulsifier is an ethoxylated fatty acid, more preferably ethoxylated oleic acid. Preferably, the composition contains from about 0.5 to 2 weight percent of the emulsifier.

Preferably, sufficient water is included in the ink so that the viscosity of the ink, measured on a Haake CV-100 Rotovisco viscometer, at 300 sec⁻¹ and 2^f ?., is between about 20 cps and £ cps. If t viscosity is too low, the composition may exhibit excessive ink flow in ball point pens. If the viscosity is too high, the ink may exhibit performance problems, e.g., blobbing, splitting and inadequate ink flow during writing.

Other conventional ingredients may be included in the composition, e.g., biocides and surfactants.

A preferred procedure for preparing the preferred compositions, which contain an oil, is to provide the pigment in the form of a dispersion and the acrylic in the form of an emulsion, premix these and the other ingredients of the composition, and pass the resulting mixture through a homogenizer which includes a liquid jet interaction chamber, such as that commercially available from Microfluidics, Newton, Mass., under the tradename MICROFLUIDIZER Model M-110Y at approximately 8000 psi. Other types of homogenizers may be

5

10

15

20

25

30

35

- 9 -

used, provided they are capable of forming a microemulsion. Preferably, the microemulsion is cooled to approximately room temperature, e.g., by passage through cooled coils, after it leaves the liquid jet interaction chamber. Multiple passes through the homogenizer may be desired in order to obtain a microemulsion having optimal stability.

In an alternate embodiment, only the oil and water (and, preferably, an emulsifier) are microemulsified, using the same microemulsifying procedure described above. The resulting oil-in-water microemulsion is then mixed with the other components of the composition using conventional mixing techniques.

Compositions of the invention which do not contain an oil need not be microemulsified, but can instead be mixed using conventional techniques.

In compositions which contain a pH dependent thickener and a base (with or without an oil), it is preferred that the pH dependent thickener alone be premixed with water (or water and any acidic to neutral pH ingredients) before exposure to the base and/or any ingredients having a basic pH. If added directly to a solution having a basic pH, without prior dilution in water, the pH dependent thickener may tend to agglomerate or clump.

An ink composition was prepared having the formulation shown in Table 1. The composition was prepared using the following procedure. First, an oil-in-water microemulation was formed by processing 40 parts linseed oil, 58 parts water, and 2 parts TRYDET 2676

5

10

15

30

surfactant (emulsifier) through a MICROFLUIDIZER Model M-110Y homogenizer at approximately 8000 psi for 3 passes. Between each pass the exit stream was cooled by passing it through the coils of the homogenizer, which were immersed in an ice water bath. Then, the POLYPHOBE thickener was premixed with a portion of the water, and this mixture was mixed with 37.5 parts of the oil-in-water microemulsion, and the remaining ingredients of the composition, using a laboratory magnetic stirrer. The resulting ink composition was placed in a ball point pen, and used to make markings on a paper substrate. The markings exhibited excellent uniformity and color intensity. The pen itself was observed to have superior writing smoothness.

TABLE 1

÷	Ingredient	Weight percent
	RHOPLEX AC 261 emulsion	40
20	Linseed oil	15
•	TRYDET 2676 emulsifier	0.75
	POLYPHOBE 9823 thickener	2
	HEUCOSPERSE III dispersi	on 15
	SILWET L7001 surfactant	0.5
25	TRYFAC 5571 surfactant	0.5
	water	26.25

Other embodiments are within the claims. For example, the inks may be used in other types of pens, .g., capillary feed rolling ball pens.

- 11 -

CLAIMS

1. A method of making an ink composition comprising the steps of:

mixing a film forming polymer, a pigment, water, and an oil to form an ink precursor; and

5

10

25

35

processing the ink precursor in a homogenizer to form an microemulsion.

2. A method of making an ink composition comprising the steps of:

mixing a pH dependent thickener, a base, a pigment, water, and an oil to form an ink precursor; and

processing the ink precursor in a homogenizer to form an microemulsion.

3. A method of making an emulsion ink comprising the steps of:

mixing an oil and water to form a mixture;

20 processing the mixture in a
 homogenizer to form an oil-in-water emulsion;
 and

blending the oil-in-water emulsion with a film forming resin, pigment and water to form an ink composition.

4. A method of making an emulsion ink comprising the steps of:

mixing an oil and water to form a mixture;

30 processing the mixture in a homogenizer to form an oil-in-water emulsion; and

blending the oil-in-water emulsion with a pH dependent thickener, a base, pigment and water to form an ink composition.

5. A method of claim 1 or 3, further comprising the step of adding a pH dependent

thickener and a base to the ink composition.

- 6. A method of claim 1 or 3, wherein said film forming polymer is an acrylic.
- A method of claim 1, 2, 3 or 4,
- 5 wherein said oil is a drying or semi-drying oil.
 - 8. A method of claim 7, wherein said oil is a vegetable oil.
 - 9. A method of claim 8, wherein said vegetable oil is linseed oil.
- 10 10. A method of claim 2 or 4, wherein said pH dependent thickener is an acid stabilized acrylic resin.
 - 11. A method of claim 1, 2, 3 or 4, further comprising the step of adding an
- emulsifier prior to processing in said homogenizer.
 - 12. A method of claim 1, wherein said ink precursor comprises from 5 to 30 weight percent of a film forming polymer, from 2 to 10 weight
- 20 percent of said pigment, from 1 to 5 weight percent of a pH dependent thickener and from 10 to 25 percent of said oil.
 - 13. An aqueous pen ink comprising a film forming polymer, a drying or
- 25 semi-drying oil, a pigment, and water.

30

- 14. An aqueous pen ink comprising a pigment, a pH dependent thickener, a base, and water.
- 15. An ink of claim 14, further comprising a drying or semi-drying oil.
 - 16. An ink of claim 14 or 15, further comprising a film forming polymer.
 - 17. An ink of claim 16, wherein said polymer is an acrylic.
- 35 18. An ink of claim 13 or 15, wherein said oil is a vegetable oil.
 - 19. An ink of claim 13 or 15, wherein a

- 13 -

portion of said water and said oil are processed in a homogenizer to form a microemulsion prior to adding said oil to said ink.

- 20. An ink of claim 13 or 15, wherein said ink is formed by mixing said components to form an ink precursor and processing said ink precursor in a homogenizer.
 - 21. A pen comprising

an outer body wall defining an ink
reservoir, the reservoir containing an ink
comprising an oil, a pigment, a film-forming
polymer, and water; and

a tip in fluid communication with said reservoir for delivering said ink to a substrate.

22. A pen comprising

15

20

25

35

an outer body wall defining an ink reservoir, the reservoir containing an ink comprising a pigment, a pH dependent thickener, a base, and water; and

a tip in fluid communication with said reservoir for delivering said ink to a substrate.

- 23. A pen of claim 21 or 22, further comprising a socket disposed at said tip and a ball mounted in said socket.
 - 24. A pen of claim 22, further comprising a drying or semi-drying oil.
- 25. A pen of claim 22 or 24, further comprising a film forming polymer.
 - 26. A pen of claim 21 or 24, wherein said oil is a vegetable oil.
 - 27. A pen of claim 21 or 24, wherein a portion of said water and said oil are processed in a homogenizer to form a microemulsion prior to adding said oil to said ink.
 - 28. A pen of claim 21 or 24, wherein said

- 14 ·

ink is formed by mixing said components to form an ink precursor and processing said ink precursor in a homogenizer.

INTERNATIONAL SEARCH REPORT

International application No. PCT/US94/11710

						
A. CLASSIFICATION OF SUBJECT MATTER						
IPC(6) :C09D 11/18; C08L 91/02; B43K 7/01						
	:106/23E, 23R; 523/161; 524/313; 401/209					
According to International Patent Classification (IPC) or to both national classification and IPC						
B. FIELDS SEARCHED						
Minimum documentation searched (classification system followed by classification symbols)						
U.S. : 106/23E, 23R; 523/161; 524/313; 401/209						
Documenta	tion searched other than minimum documentation to th	e extent that such documents are included	in the fields searched			
NONE		•				
Binetennia	late have accorded dust a shell-second at the					
]	data base consulted during the international search (n	ame of data base and, where practicable,	, search terms used)			
NONE						
ĺ						
C. DOC	CUMENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where a	ppropriate, of the relevant passages	Relevant to claim No.			
Υ	US, A, 5,004,763 (IMAGAWA) (02 April 1991 column 1	1-28			
*	lines 10-52; column 2, lines 4-62		1-20			
	Inles 10°52, Coldini 2, Inles 4°02	, column 3, lines 0-03.				
	NC A 4 000 404 (0) (5N) 00 0		4.00			
Υ,	US, A, 4,960,464 (CHEN) 02 Octo	ober 1990, column 1, lines	1-20			
· .	15-68; column 2, lines 1-11.					
Υ	US, A, 4,410,643 (MULLER) 18	October 1983, column 1,	1-28			
	lines 32-63; column 2, lines 61-					
	column 4, lines 22-68; column 5					
	lines 1-12.	,				
•						
Υ	LIC A 4 001 E17 ID-CANTO	ID \ 01 Inn. 1001	1 20			
r	US, A, 4,981,517 (DeSANTO,	JK,) 01 January 1991,	1-20			
	column 2, lines 10-25.					
, ,			•			
	•	\cdot				
		·	**			
Y Further documents are listed in the continuation of Pay C						
X Further documents are listed in the continuation of Box C. See patent family annex.						
	ecial categories of cited documents:	"T later document published after the inte date and not in conflict with the applica	rtion but cited to understand the			
"A" doc	nument defining the general state of the art which is not considered be part of particular relevance	principle or theory underlying the inve	ention			
.E. car	lier document published on or after the international filing date	"X" document of particular relevance; the considered novel or cannot be consider				
"L" doc	nument which may throw doubts on priority claim(s) or which is	when the document is taken alone	m mannac am matemac arch			
cita	d to establish the publication date of another citation or other cial reason (as specified)	"Y" document of particular relevance; the	s claimed invention cannot be			
-	rument referring to an oral disclosure, use, exhibition or other	considered to involve an inventive combined with one or more other such	step when the document is			
me	uns	being obvious to a person skilled in th				
	nument published prior to the international filing date but later than priority date claimed	*&" document member of the same patent	family .			
Date of the actual completion of the international search Date of mailing of the international search report						
0.3 MAR 1995						
09 FEBRUARY 1995						
Name and mailing address of the ISA/US Authorized officer						
Commissioner of Patents and Trademarks						
Box PCT Washington, D.C. 20231 PAUL MICHL						
Facsimile No		Telephone No. (703) 308-2351	-			

Form PCT/ISA/210 (second sheet)(July 1992)*

INTERNATIONAL SEARCH REPORT

International application No. PCT/US94/11710

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	
?	US, A, 5,120,359 (UZUKAWA) 09 June 1992, column 1, lines 9- 24; column 2, lines 20-68; column 3, lines 3-54; column 4, lines 1-54.	1-20	
	·		
	· ·		
		•	
	·		
İ		•	
		•	
•	•		

Form PCT/ISA/210 (continuation of second sheet)(July 1992)*